

Type	Micro Controller based True RMS sensing and correction.
Model	AL 415/200-220V
Input Regulation Range	415 V
Output Voltage	200-220V
Input frequency range	47 Hz to 53 Hz.
Type of cooling	Air Cooled
Average correction rate	60V per/sec
Servo motor drive	Triac based drive for AC Step Synchronous motor
Efficiency	Better than 98%

Commercial Offer:

Rating/Model	Description	Qty.	Best Rate/Unit	Total
20KVA ISOLATION TRANSFORMER 3-PHASE K1 (Step down)	KRYKARD: 3ph, Step Down Isolation Transformer, Air Cooled, Delta-Star winding Unbalanced type, Input Regulation Range: 415V. Output Voltage: 200-220V		47000.00 43000	47000.00

089 258 17142
No. Altmash

CHECK LIST

DISCOUNTED Rate as above
FOR-JAL Bhivadi.

PRICE BASIS : FOR BHIVADI

P & F : INCL / EXTRA

GST/IGST : 18% Extra

DELIVERY : 2-3 weeks

PAYMENT : 30 days credit

WARRANTY : 24 months from the date of sup.

VALIDITY : 90 days

CHECKED BY : Rajaraj

Other Terms & Conditions:

Order placement	In favour of: Atandra Energy Private Limited, No. 5, Kumaran Street, Pazhavanthangal, Chennai 600114
Freight	-
Sales Tax	GST @18% Extra. HSN Code - 90328910
Delivery	1-2 weeks from date of receipt of Purchase order
Payment	With in 30 days of Delivery
Guarantee	24 months from the date of supply against manufacturing defects.
Validity	90 days from date of quotation

Following requirements in Buyers/End Users scope:

- Handling equipment and labor to be arranged for unloading of the product during delivery (or for lifting of product from oil tank in case of oil cooled products during installation or service).
- Provision, laying & termination of power cables to the product along with suitable lugs, glands, electrical sockets, switches and other accessories that may be required as per site conditions.
- Short Circuit Protection for ratings above 100 kVA: External MCCB to be provided for short circuit protection.
- For isolation transformers: a dedicated earth to be provided for connection to output neutral terminal of the transformer.