



JINDAL ALUMINIUM LTD (ROLLING MILL DIVISION).

KIADB IND.AREA, Tumkur Road,Dabaspete,Bangalore-562111

Product Name:	ALUMINIUM SHEET		
Specification:	0.3 to 6 mm thickness		
Alloy & Temper	AA-3003	Temper	0, H12 OR H22 , H14 OR H24, H16 OR H26, H18 OR H28

CERTIFICATE OF ANALYSIS

PHYSICAL & MECHANICAL PROPERTIES					
SL.NO	DESCRIPTION	UNIT	LIMITS	OBSERVATION	
1	Alloy & Temper	-----	-----	AA-3003	0
2	U.T.S	MPa	95 - 135 Mpa	Complies	
3	Yield Strength	MPa	35 (Min)	Complies	
4	Elongation	%	Minimum- 20 - 25 % (As per thickness)	Complies	
PHYSICAL & MECHANICAL PROPERTIES					
SL.NO	DESCRIPTION	UNIT	LIMITS	OBSERVATION	
1	Alloy & Temper	-----	-----	AA-3003	H12 OR H22
2	U.T.S	MPa	115 - 160 Mpa	Complies	
3	Yield Strength	MPa	80 (Min)	Complies	
4	Elongation	%	Minimum- 6 - 9% (As per thickness)	Complies	
PHYSICAL & MECHANICAL PROPERTIES					
SL.NO	DESCRIPTION	UNIT	LIMITS	OBSERVATION	
1	Alloy & Temper	-----	-----	AA-3003	H14 OR H24
2	U.T.S	MPa	140 - 180 Mpa	Complies	
3	Yield Strength	MPa	115 (Min)	Complies	
4	Elongation	%	Minimum- 4 - 6 % (As per thickness)	Complies	
PHYSICAL & MECHANICAL PROPERTIES					
SL.NO	DESCRIPTION	UNIT	LIMITS	OBSERVATION	
1	Alloy & Temper	-----	-----	AA-3003	H16 OR H26
2	U.T.S	MPa	165 - 205 Mpa	Complies	
3	Yield Strength	MPa	140 (Min)	Complies	
4	Elongation	%	Minimum- 3 to 4%(As per thickness)	Complies	
PHYSICAL & MECHANICAL PROPERTIES					
SL.NO	DESCRIPTION	UNIT	LIMITS	OBSERVATION	
1	Alloy & Temper	-----	-----	AA-3003	H18 OR H28
2	U.T.S	MPa	180 Mpa (Min)	Complies	
3	Yield Strength	MPa	165 (Min)	Complies	
4	Elongation	%	Minimum- 2 to 3%(As per thickness)	Complies	
DIMENSIONAL TOLERANCES					
1	Thickness	mm	0.3 to 0.91 mm - (+/- 0.02 mm), 0.92 to 1.4 mm-(+/-0.03 mm) , 1.41 to 2 mm (+/- 0.04 mm) , 2 to 3 mm (+/-0.050 mm) , 3.01 to 4 mm (+/- 0.075 mm) , 4.01 to 6 mm (+/- 0.1 mm)		
2	Width	mm	For 12.5 to 152.4 mm (+/-0.25 mm), For 152.4 to 304.8 mm(+/-0.4 mm) , For 304.8 to 609.6 (+/-0.8mm), For 609.6 to 1219.2 mm - (+/-1 mm) , For 1219.2 to 1524 mm (-1 / + 2 mm)		
3	Length	mm	≤ 1220 mm - (+/-2 mm) , 1220 to 2440 mm - (+ / - 3 mm), 2440 to 3660- (-3 / + 5 mm) , ≥ 3660 mm (-4 / + 7 mm)		
ALLOY COMPOSITION:					
AA	Si	Fe	Cu	Mn	Mg
AA-3003	0.6 (Max)	0.7 (Max)	0.05 - 0.2	1 - 1.5	0.1 (Max)
Cr	Zn	Ti	Others	Al	
--	0.1 (Max)	--	-	Remainder	

REMARKS: THE CHEMICAL COMPOSITION AND MECHANICAL PROPERTIES MEETS AS PER -IS737-2008

PRATIK
PREPARED BY
(Executive Q.A)

R KRISHNA PRASAD
APPROVED BY:
(Head Of Q.A)