






TECHNICAL DATA SHEET

	TDS No.	Date : 06/09/2021
1	NAME OF CUSTOMER :	BHAVYA STEEL
2	PRODUCT	ALUMINIUM SHEET
3	END APPLICATION	GLAZING
4	PRODUCT SPECIFICATIONS	2 mm x 1220 mm x 2440 mm
5	ALLOY	AA 1060
6	TEMPER	H14
7	TOLERANCES	
a)	THICKNESS TOLERANCE(mm)	+/-0.2mm
b)	WIDTH TOLERANCE(mm)	+/- 1 mm
c)	LENGTH TOLERANCE (mm)	+/- 3 mm
8	Edge Burr (%)	Maximum 3%
9	TENSILE STRENGTH (MPa)	95-125 MPa
10	Elongation %	Minimum 6%
11	Anodizing	No
12	Powder coating	No
13	Bending	90° Pass (1 T)
14	Chemical Composition	EN 573-3
15	Surface Finish	Free from any surface defects. No scratches, handling marks. Bare uncoated sheets with mill finish.
16	Edges	Trimmed/Fine/Right-angled Edge
17	PACKING REQUIREMENTS	As per PO
18	INTERLEAVING	Yes. LDPE Interleaving
19	MASKING	No
20	MOQ	4 MT
21	SPECIAL REQUIREMENTS	Standard HDPE pallet packing
	For BHAVYA STEEL	ACCEPTED
	For 	Process review Committee
	PARTNER	   
	Name & Designation of Customer Rep.	JINDAL ALUMINIUM LIMITED Rolling Mill Division, K. J. A. D. S. Industrial Area Yedahalli Village, Tumkur Road Dabbaspet, Bengaluru-562 111 Ph: 080-27735051-27735003