## **TECHNICAL DATA SHEET**

	DS No.	Date : 29-10-2020
1 N	AME OF CUSTOMER :	DALFO FLEXIPACK PRIVATE LIMITED
2 PF	RODUCT	SRC Aluminium Foil
3 EN	ND APPLICATION	Aluminium Foil container
	RODUCT SPECIFICATIONS LLOY	8006
5 TE	EMPER	H24
6 DI	IMENSIONS & TOLERANCE	Thk Tolerance: +/-3 %, Width Tolerance: +/-1 mm
	HICKNESS (mm)	0.037
	/IDTH (mm)	
D) VV	MOTE (HIIII)	As per AO
7 CC	OIL DIAMETER (mm)	
		153 man (Charle alternation and
	ternal Diameter of coil (mm)	152 mm, (6 inch aluminium core)
	/pe of core	Aluminium core
c) M	aximum Outer Diameter of coil (mm)	As per AO
0 1 5	11221	
	oil Weight (Min,/Max)	As per OD
b) Co	oil Build up	Uniform. Build up difference: +/-0.5 mm
9 Su	urface (BSO/DSO/BSB)	BSB (Both side Bright)
10 TE	NSILE STRENGTH(Mpa)	125-140
11 El	ongation( %)	8 Minimum
12 Fr	eefall (m)	Max 2 m, length unwind free fall. As per standard EN546-4
13 W	ettability	NA NA
14 Pi	n Holes	Maximum '0' nos/Sq.M
15 Ch	nemical Composition	AS PER STD NO ASTM B209M/EN573-3/IS737:2008 AND AS APPLICABLE
16 Su	ırface Finish	Dent free, scratch free
17 Ty	pe of Joint	Tape joint
18 Jo	int Identification	Flag mark near Joint
19 No	o of Joints	70% of order Qty '0' Joints, 20% of Order Qty '1' Joint, 10% of order Qty '2' Joints- Maximum
20 Ed	lges	Trimmed
21 SP	PECIAL PACKING REQUIREMENTS	Wooden Pallet packing
22 Sta	andard used for foil	IS15392 , IS13237 , EN 546-2:2006 , IS737:2008
		ACCEPTED
Fo	or .	ACCEPTED  For Jindal Aluminium Limited (Rolling D
. 10		roi Jindai Aluminium Limited (Kolling D
		De la
Na	ame & Designation of Customer Rep.	Name & Designa

(Rolling Mill Division)
K.I.A.D.B. Industrial Area
Yedahalli Village, Tumkur Road
Dabbaspet, Bengaluru-562 111
Ph: 080-27735051-27735003

30/X