

TECHNICAL DATA SHEET

Date : 23-09-2020

TDS No.	
1	NAME OF CUSTOMER : EZEE PACK
2	PRODUCT SRC Aluminium Foil
3	END APPLICATION Aluminium Foil container
PRODUCT SPECIFICATIONS	
4	ALLOY 8006
5	TEMPER H24
6	DIMENSIONS & TOLERANCE Thk Tolerance: +/-5%, Width Tolerance: +/-1 mm
a)	THICKNESS (mm) 0.032-0.042
b)	WIDTH (mm) As per AO
7	COIL DIAMETER (mm)
a)	Internal Diameter of coil (mm) 152 mm, (6 inch aluminium core)
b)	Type of core Aluminium core
c)	Maximum Outer Diameter of coil (mm) As per AO
8 a)	Coil Weight (Min./Max) As per OD
b)	Coil Build up Uniform. Build up difference: +/-0.5 mm
9	Surface (BSO/DSO/BSB) BSB (Both side Bright)
10	TENSILE STRENGTH(Mpa) 125-140
11	Elongation(%) 8 Minimum
12	Freefall (m) Max 2 m, length unwind free fall. As per standard EN546-4
13	Wettability NA
14	Pin Holes Maximum '0' nos/Sq.M
15	Chemical Composition AS PER STD NO.- ASTM B209M/EN573-3/IS737:2008 AND AS APPLICABLE
16	Surface Finish Dent free, scratch free
17	Type of Joint Tape Joint
18	Joint Identification Flag mark near Joint
19	No of Joints 70% of order Qty '0' Joints, 20% of Order Qty '1' Joint, 10% of order Qty '2' Joints- Maximum
20	Edges Trimmed
21	SPECIAL PACKING REQUIREMENTS Wooden Pallet packing
22	Standard used for foil IS15392, IS13237, EN 546-2:2006, IS737:2008
ACCEPTED <i>R. Venishwari Prasad</i>	
For _____ For Jindal Aluminium Limited (Rolling Div.)	
<i>R. Venishwari Prasad</i>	
<i>DGM - AA</i>	
Name & Designation of Customer Rep.	



JINDAL ALUMINIUM LTD.
 (Rolling & Extrusion Division)
 Plot No. 1 & 2, (Part)
 Yedehalli Village, Somaswamy Hobli
 BANGALORE - 560022
 Phone: 080-27711111, 27711112, 27711113
 Our GSTIN: 29AAAC3123L1Z0