* TECHNICAL DATA SHEET

	TDS No.	Date: 09/09/2020
1	NAME OF CUSTOMER :	Glass Wall Systems
2	PRODUCT ,	Aluminium Sheet
3	END APPLICATION	Building architecture
	PRODUCT SPECIFICATIONS	2002
-4	ALLOY	3003
5	TEMPER	H14
6	CHEMICAL COMPOSITIONS	AS per IS Standard
7	DIMENSIONS & TOLERANCE	
a)	THICKNESS (mm)	0.91 mm to 4 mm, for 0.91(Tol: ±0.020mm) & 4.00 (Tol: +/-0.1 m
b)	WIDTH (mm)	900 mm to 1550 - (Tolerance +/- 1mm upto 1220mm) (Tolerance : -1/+2mm ≥1220mm)
cl	Length (mm)	1500 mm to 5000 -(Tolerance : +/- 2 mm upto 1220 mm & +/- 3n for 1220 to 3000 mm & +5mm/-3mm for above 3000 mm)
	Dia(mm) - FOR CIRCLE	N/A
	COIL DIAMETER	N/A
	Internal Diameter of coil (mm)	N/A
	Maximum Outer Diameter of coil (mm)	N/A
9 a)	Coll Weight (Min,/Max)	250 kg bundle weight
	Coil Build up	N/A
10	TENSILE STRENGTH	AS per IS Standard
12	Elongation	AS per IS Standard
13	Resistivity	NA .
13		
14	Surface Finish	SMOOTH, FLAT & GOOD SURFACE FINISH WITHOUT ANY PIT/DENT/BLACK/WHITE SPOT & SCRATCHES
15	Edges	FINE
16	SPECIAL PACKING REQUIREMENTS	Standard HDPE Packing
.10		
17	SPECIAL REQUIREMENT	
		ACCEPTED FLANG
	2	
	For	ACCELLED (VOZ.)
	For	For Jindal Aluminium Limited (Rolling R. Knishna Pros

MKOAL ALLIMINIUM 177).