## TECHNICAL DATA SHEET

T	DS No.	Date: 13.08.2020
1 N	AME OF CUSTOMER :	Honylite private limited
		ALUMINIUM SHEET
2 PI	RODUCT	ALUMINIUM SHEET
	11 2 3 6 1 2 5 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 1 2 3 1 2	Honeycomb Panel
3 EI	ND APPLICATION	noneycomb ranei
	RODUCT SPECIFICATIONS	1 x 1525 x 2440 mm, 1 x 1525 x 3050 mm, 1 x 1220 x 2440 mm
P	RODUCT SPECIFICATIONS	
1 1	ILLOY	3003
4 4	eco.	
5 T	EMPER	H26
	AP31 - 590 -	
6 D	DIMENSIONS & TOLERANCE	
a) T	THICKNESS (mm)	1 MM (Tolerance +/- 0.030 mm)
-	NIDTH (mm)	1525 MM , 1220 MM (Tolerance +/- 1 mm)
		2440 MM , 3050 MM (Tolerance : - + / - 3 mm)
c) L	ength (mm)	2440 WIM , 5050 WIM (1010.5.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1
7.0	COIL DIAMETER	NA (
	Internal Diameter of coil (mm)	NA 3
b) [	Maximum Outer Diameter of coil (mm)	NA NA
5) 1	VIAXIII dili Gutti Didili etc. G. Co. (1)	
8 a) (	Coil Weight (Min,/Max)	+ / - 10 %
	Coil Build up	NA NA
10	Elongation	3 % Min
10	Elongation	
11	Resistivity	NA
12	Chemical Composition	As per IS737:2008 (Composition range- Si-0.6(Max), Fe-0.7(Max), Cu-0.05 to 0. Mn-1 to 1.5, Mg-0.1 (Max), Cr-trace, Zn-0.1(Max), Ti-trace, Al-Remainder)
		Will-1 to 1.5 , Wig o.1 (Waxy ) or trass, and a
	1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2	
13	Surface Finish	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO
13	Surface Finish	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT , as per PO
	Surface Finish Edges	
		SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE
14	Edges	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT , as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood
14		SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT , as per PO  FINE
14	Edges	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT , as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT , as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety
14	Edges	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT , as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects Aluminium sheet should not be having rolling marks, black spots & impression
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects Aluminium sheet should not be having rolling marks, black spots & impression
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects  Aluminium sheet should not be having rolling marks, black spots & impression it
14	Edges  SPECIAL PACKING REQUIREMENTS  SPECIAL REQUIREMENT	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects  Aluminium sheet should not be having rolling marks, black spots & impressio it
14	Edges  SPECIAL PACKING REQUIREMENTS	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects  Aluminium sheet should not be having rolling marks, black spots & impressio it
14	Edges  SPECIAL PACKING REQUIREMENTS  SPECIAL REQUIREMENT	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL  Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects  Aluminium sheet should not be having rolling marks, black spots & impressio it
14	Edges  SPECIAL PACKING REQUIREMENTS  SPECIAL REQUIREMENT	SMOOTH SURFACE WITHOUT ANY SURFACE DEFECT, as per PO  FINE  AS PER PO Upper sheet always gets damaged Kindly put 12 mm thick plywood top of each pallet for safety  SUITABLE FOR HONEYCOMB PANEL Aluminium sheet should free from dent, dirt, wrinkles, water/oil brown stair and any other visual defects Aluminium sheet should not be having rolling marks, black spots & impressio it  ACCEPTED  For Jindal Aluminium Limited (Rolling



JINDAL ALUMINIUM LIMITED
(Rolling Mill Division)
K.I.A.D.B. Industrial Area
Yedehalli Village, Dabbespet
BANGALORE-562 111
Ph: 080-27735051/27735003