


## TECHNICAL DATA SHEET

	TDS No.	Date : 21/09/2021
1	NAME OF CUSTOMER :	KETAN CORPORATION
2	PRODUCT	ALUMINIUM SHEET
3	END APPLICATION	C
4	PRODUCT SPECIFICATIONS	1.5/2/2.5 mm x 1220 mm x 2440 mm
5	ALLOY	AA 1050
6	TEMPER	H14
7	TOLERANCES	
a)	THICKNESS TOLERANCE(mm)	+/- 0.05 mm [Thickness: >1.4 mm to 2 mm] +/- 0.06 mm [Thickness; >2 mm to 3 mm]
b)	WIDTH TOLERANCE(mm)	+/- 1 mm
c)	LENGTH TOLERANCE (mm)	+/- 3 mm
8	TENSILE STRENGTH (MPa)	105 - 135 MPa
9	Elongation %	Minimum 6%
10	Electrical Conductivity [% of IACS at 20° C]	Minimum 60%
11	Anodizing	Y ..... <i>NOT for final order</i>
12	Powder coating	NO
13	Bending	90° Pass [1 T]
14	Chemical Composition	As per IS 737:2008
15	Surface Finish	Free from any surface defects.
16	Edges	Trimmed/Fine/Right-angled Edge
17	PACKING REQUIREMENTS	As per AO/PO
18	INTERLEAVING	NO
19	MASKING	YES
20	MOQ	4 MT
21	Oil Carry-Over	Maximum 50 mg/Square meter
<b>For KETAN CORPORATION</b>		ACCEPTED
For	<i>Kew</i> <b>PARTNER</b>	Process review Committee
Name & Designation of Customer Rep.		 <p style="text-align: center;"> <b>SKSNDAL ALUMINIUM LIMITED</b>                  (Regional Division)                  K.I.A.D.B. Industrial Area                  Yedahalli Village, Tumkur Road                  Dabbaspet, Bengaluru-562 199                  Ph: 080-27735051-27735003             </p>

BNS  
LEAVE