






# ROCKDUDE IMPEX PVT. LTD.

## TECHNICAL DATA SHEET

TDS No.	Date : 26.05.2020	
1	NAME OF CUSTOMER :	Rockdude Impex Pvt Limited
2	PRODUCT	Manufactures of Semi Rigid containers, HouseFoil, Parchment paper, Grease Proof Paper & Cut sheet
3	END APPLICATION	Food Packaging Products
<b>PRODUCT SPECIFICATIONS</b>		
4	ALLOY	<del>3003, 8006 &amp; 8011</del>
5	TEMPER	H24 ✓
6	DIMENSIONS & TOLERANCE	2% Tolerance (+/-)
a)	THICKNESS (mm)	31 Micron to 180 Micron ± 5%
b)	WIDTH (mm)	410 MM to 802 MM
c)	Length (mm)	
7	COIL DIAMETER	
a)	Internal Diameter of coil (mm)	76 & 152 MM
b)	Maximum Outer Diameter of coil (mm)	600 MM
8 a)	Coil Weight (Min./Max)	100 kg Min to 600 kg Max
b)	Coil Build up	
9	TENSILE STRENGTH	141-150 Mpa 125 to 140 MPa
10	Elongation	10 to 20 % 8% min
11	Resistivity	<del>2.65 μΩ cm</del>
12	Surface finish	Above 30 Micron aluminium foil has a brightly polished surface on both sides. Below 20 Micron one side has a matt finish & other side shiny finish.
13	Edges	Aluminium foil with round edge and without burr X
14	SPECIAL PACKING REQUIREMENTS	Rolls will be packed in wooden boxes along with plastic bags covers as per Import raw material packaging style ✓
15	SPECIAL REQUIREMENT	Food Grade Quality Foil & also BUREAU OF INDIAN STANDARDS certified foil with IS 737 & IS15392 ✓ Material Test Certificate along with every supply of raw material ✓
For Rockdude Impex Pvt Limited		ACCEPTED For Jindal Aluminium Limited (Rolling Div.)
 Plant Manager		 R. KRISHNA PRASAD DGM - QA Name & Designation
 Name & Designation of Customer Rep		