

TECHNICAL DATA SHEET

TDS No.		Date : 23-09-2020
1	NAME OF CUSTOMER :	SHRIYA INDUSTRIES
2	PRODUCT	SRC Aluminium Foil
3	END APPLICATION	Aluminium Foil container
PRODUCT SPECIFICATIONS		
4	ALLOY	8006
5	TEMPER	H24
6	DIMENSIONS & TOLERANCE	Thk Tolerance: +/-5%, Width Tolerance: +/-1 mm
a)	THICKNESS (mm)	0.032-0.040
b)	WIDTH (mm)	As per AO
7	COIL DIAMETER (mm)	
a)	Internal Diameter of coil (mm)	76 mm, (3 inch aluminium core)
b)	Type of core	Aluminium core
c)	Maximum Outer Diameter of coil (mm)	As per AO
8 a)	Coil Weight (Min./Max)	As per OD
b)	Coil Build up	Uniform. Build up difference: +/-0.5 mm
9	Surface (BSO/DSO/BSB)	BSB (Both side Bright)
10	TENSILE STRENGTH(Mpa)	125-140
11	Elongation( %)	8 Minimum
12	Freefall (m)	Max 2 m, length unwind free fall. As per standard EN546-4
13	Wettability	NA
14	Pin Holes	Maximum '0' nos/Sq.M
15	Chemical Composition	AS PER STD NO.- ASTM B209M/EN573-3/IS737:2008 AND AS APPLICABLE
16	Surface Finish	Dent free, scratch free, Une mark free
17	Type of Joint	Tape joint
18	Joint Identification	Flag mark near joint
19	No of Joints	70% of order Qty '0' Joints, 20% of Order Qty '1' Joint, 10% of order Qty '2' Joints- Maximum
20	Edges	Trimmed
21	SPECIAL PACKING REQUIREMENTS	Wooden Pallet packing
22	Standard used for foil	IS15392, IS13237, EN 546-2:2006, IS737:2008

For *Shriya Industries*

Name & Designation of Customer Rep.

*P. K. K. Manager*

ACCEPTED

*[Signature]*  
For Jindal Aluminium Limited (Rolling Div.)

*[Signature]*  
JINDAL ALUMINIUM LIMITED

(Rolling & Extrusion Division)

Plot No. 1 & 2, (Part)

Yedehalli Village, Sompura Hobli

BANGALORE RURAL-562 111

Phone: 080-27235051-27235003

Our GSTIN: 29AAAAC1414M112D