

TECHNICAL DATA SHEET

TDS No.		Date : 19-09-2020
1	NAME OF CUSTOMER :	Sliver Foil pvt ltd
2	PRODUCT	SRC Aluminium Foil
3	END APPLICATION	Aluminium Foil container
PRODUCT SPECIFICATIONS		
4	ALLOY	8006
5	TEMPER	H24
6	DIMENSIONS & TOLERANCE	Thk Tolerance: +/-5%, Width Tolerance: +/-1 mm
a)	THICKNESS (mm)	0.034,0.036,0.038
b)	WIDTH (mm)	503,588,603,632
7	COIL DIAMETER	As per Ordered Dia
a)	Internal Diameter of coil (mm)	76 mm, (3 inch aluminium core)
b)	Type of core	Aluminium core
c)	Maximum Outer Diameter of coil (mm)	500
8 a)	Coil Weight (Min./Max)	As per OD
b)	Coil Build up	Uniform. 70% of order Qty '0' Joints, 20% of Order Qty '1' Joint, 10% of order Qty '2' Joints
9	Surface (BSO/DSO/BSB)	BSB
10	TENSILE STRENGTH Mpa	125-140
11	Elongation %	8% Miniumum
12	Wettability	NA
13	Bursting strength	NA
14	Pin Holes	Zero
15	Chemical Composition	AS PER STD-NO.- ASTM B209M/EN573-3/IS737:2008 AND AS APPLICABLE
16	Surface Finish	Dent and scratch free
17	Edges	Trimmed
18	SPECIAL PACKING REQUIREMENTS	Pallet packing only.
19	SPECIAL REQUIREMENT	No oil patch, No oil carry over,Good hardness not to crack at time of punching
20	Standard used for foil	IS15392 , IS13237 , EN 546-2:2006 , IS737:2008
For		ACCEPTED <i>[Signature]</i> For Jindal Aluminium Limited (Rolling Div.)
Name & Designation of Customer Rep.		<i>[Signature]</i> 797-9A Name & Designation