TDS No.	Date: 29/07/202
NAME OF CUSTOMER:	SPEARHEAD BUSDUCTS PR ATE LIMITED
NAME OF SOSTOMER.	SPEARHEAD BUSDUCTS FR. ATE LIMITED
PRODUCT	ALUMINIUM SHEET
END APPLICATION	Sheet metal fabrication
	5 mm x 1500 mm x 3000 mm
TRODUCT STEERINGATIONS	3 Hill X 1300 Hill X 3000 Hill
ALLOY	8011
TEMPER	H14
CHEMICAL COMPOSITION	As per IS 737:2008
CHEWICAL COWF OSTHOW	A3 per 13 737.2000
TOLERANCES	
THICKNESS TOLERANCE (mm)	As per IS 2676
ALIENTANIE POR TENERAL III PRINCIPALINIA PRINCIPA	As per IS 2676
LENGTH TOLERANCE (mm)	As per IS 2676
ANODIZING	NO
POWDER COATING/PAINTING	NO
TENSILE STRENGTH	125 -160 MPa
Flongation(%)	Minimum 5%
Bending	90° pass [1T]
Electrical Conductivity (% IACS at 20°C)	Minimum 55.5%
Surface Finish	Free from any surface defects
Edges	Trimmed/Right angle edges
Packing Requirements	Standard sheet HDPE pallet packing
	END APPLICATION PRODUCT SPECIFICATIONS ALLOY TEMPER CHEMICAL COMPOSITION TOLERANCES THICKNESS TOLERANCE (mm) WIDTH TOLERANCE (mm) ENGTH TOLERANCE (mm) ANODIZING POWDER COATING/PAINTING TENSILE STRENGTH Elongation(%) Bending Electrical Conductivity (% IACS at 20°C)

Satish Digitally signed by Satish Patnaik Date: 2021.07.30 O8:30:45 +05'30'

(Rolling Mill Division)

K.I.A.D.B. Industrial Area

Yedahalli Village, Tumkur Road

Dabbaspet, Bengaluru-562 111

Ph: 080-27735051-27735003