

1st time, on trial basis only as per DM Sir's mail.

Material requirement data sheet for Aluminium sheet	
TDS No. NHTL/MAY20/01	Date: 25/09/2020
Customer Name	SRI POOVATHAL POLYMERS
Product	ALUMINIUM SRC FOIL
End Application	SRC FOIL CONTAINER
Thickness (range)	
	0.033 mm – 0.040 mm
Width (range)	
	300 mm – 900 mm
Length	
	-
Alloy	
	8006
Temper	
	H24
Coil Core	
1. Core ID	3"
2. Core Type	With Aluminium core
Aluminium sheet finish	
1. Dead flat	-----
2. Flat material	-----
3. Deep drawing	-----
Aluminium Sheet Tolerances in MM, if not critical JAL will supply as per IS standard	
1. Thickness tolerance	+/- 3% (it should not go beyond this)
2. Width tolerance	+ / - 1 mm
3. Length tolerance	-----
4. Squareness tolerance	-----
5. Quantity tolerances	+/- 5%
Aluminium Sheet mechanical properties	
Tensile strength	125 – 140 MPa
Elongation	8% (min)
Resistivity (Max)	-----
Conductivity (Min)	-----
Aluminium Coil Packing	
1. Bundle weight	300 kgs – 400 kgs
2. Packing type	HDPE + Wooden Pallet

Surface	Surface should be free from all defects. Any defect with respect to surface will lead to rejection.
Special Requirement	Single bundle on single wooden pallet
Chemical Composition	As per IS 737 - 2008

For Sri Poovathal Polymers	For Jindal Aluminium Limited (Rolling Div.)
Name & Designation of Customer Rep.	Name & Designation :- KARTHIK (DIRECTOR)
Seal & Signature	Seal & Signature B. K. M. L. I. J.

For SRI POOVATHAL POLYMERS,

JINDAL ALUMINIUM LIMITED
 (Rolling Mill Division)
 K.I.A.D. Industrial Area,
 Yeddiur Village, Hyderabad
 District, Andhra Pradesh

[Signature]
 29/09/20

Partner.