

TECHNICAL DATA SHEET

	TDS No.	Date: 04.03.2021
1	NAME OF CUSTOMER :	STARCORE REFREIGERATIONS LIMITED
	PONO	SCGST/00610-DT 26.02.2021
2	PRODUCT	Coils
3	END APPLICATION	REFRIGERATION
	PRODUCT SPECIFICATIONS	
4	ALLOY	8011
5	TEMPER	"O"
6	DIMENSIONS & TOLERANCE	
a)	THICKNESS	0.4 mm (Tol. +/- 25MIC)
b)	WIDTH	325 mm (Tol. +/- 0.794 mm)
c)	Length	N/A
7	COIL DIAMETER	
a)	Internal Diameter of coil (mm)	76
b)	Maximum Outer Diameter of coil (mm)	OD AS PER WEIGHT-400KG MAX
8 a)	Weight (Min./Max)	
b)	Coil Weight	400KG MAX
c)	Packing	BOX
9	TENSILE STRENGTH	85-120 MPA
10	Elongation %	19% MIN
10A	BEND TEST	
11	Resistivity	N/A
12	Surface Finish	FREE FROM SCRATCH, BURST & CONTAMINATION
13	Edges	Smooth
14	SPECIAL PACKING REQUIREMENTS	BOX
	PROFILE	
15	SPECIAL REQUIREMENT	
16	IS SPECS	IS Standard 737:2008
	For	ACCEPTED For Jindal Aluminium Limited (Rolling Div.)

Starcore Refrigeration Limited

Authorized signatory

JINDAL ALUMINIUM LIMITED
 Rolling Mill Division
 B. Industrial Area
 Yashwanth Village, Tumkur Road
 Dattarajpet, Bengaluru-562 111
 Phone: 080-27735051-27735003