



## TECHNICAL DATA SHEET

	TDS No.	Date : 12/07/2021
1	NAME OF CUSTOMER :	SUNSHINE TECHNOLOGIES
2	PRODUCT	ALUMINIUM SHEET
3	END APPLICATION	GEQ
4	PRODUCT SPECIFICATIONS	2.5 mm x 1220 mm x 1830/2440 mm
5	ALLOY	AA 8011 ✓
6	TEMPER	H14
7	CHEMICAL COMPOSITION	As per IS 737:2008
8	<b>TOLERANCES</b>	
a)	THICKNESS TOLERANCE (mm)	+/- 0.06 mm
b)	WIDTH TOLERANCE (mm)	+ / -1 mm
c)	LENGTH TOLERANCE (mm)	+ / -3 mm
9	ANODIZING	NO
10	POWDER COATING/PAINTING	NO
11	TENSILE STRENGTH	125-160 MPa
12	Elongation(%)	Minimum 4 %
13	Bending	90° pass
14	Surface Finish	Smooth, flat and good surface finish without any pit, dent, black, white spot & scratches
15	Edges	Trimmed
16	Packing Requirements	Standard pallet packing
For Sunshine Technologies		ACCEPTED
For		Process review Committee
	Proprietor	 <b>SKS JINDAL ALUMINIUM LIMITED</b> Rolling Mill Division K.I.A.D.B. Industrial Area Yedahalli Village, Tumkur Road Dabbaspet, Bengaluru-562 111 Tel: 27735051-27735005
	<b>V. GURURAJ</b>	
Name & Designation of Customer Rep.		

**SUNSHINE TECHNOLOGIES**  
 # 84, 3rd Cross, Saibabanagar,  
 Srirampuram,  
 Bangalore - 560 021.