



V-0.4X90°
CH-0.6X45°

CODE : SEW/OME/S1/ 1022
REV : 00 / Dt : 13.12

NOTE:- ALL DIMENSIONS ARE IN mm.

UNSPECIFIED RADIUS:-0.50

UNSPECIFIED TOLERANCES WILL BE IN ACCORDANCE WITH DIN ISO 2768-1 class C = Coarse		30-120	120-400	400-1000		
		±0.8	±1.2	±2.0		
Dimension	0.5 - 3	3 - 6	6 - 30	30-120	120-400	over 400
Longitudinal	±0.2	±0.3	±0.5	±0.8	±1.2	±2.0
chamfer & radius	0.5 - 3	3 - 6	6 - 30	30-120	120-400	over 400
Degrees & Minutes	at 10	±1°	±1.0	±2.0	±0.8	±0°10'

OMALCO EXTRUSION PVT LTD		
AREA:- 196.866 Sqmm [^]	ALLOY/TEMPER:- 6063 T6	DRAWN BY: RAJE
EX PERIMETER:- 235.161 mm.	FLATNESS:-±0.8mm [^]	DATE: 13/12/2019
WEIGHT:- 1.945 Kg/12'	TOLERANCES:	REVISION:-
DESCRIPTION :	ANGULARITY:-±2°	CHECKED BY:-
PARTY DRG NO:	straightness:-1.70meter	APPROVED BY:-
SECTION NO: 9138	TWIST:-1.70mm/meter	SCALE:- 2:1

D:/SUDHEER ENGG/2019/NS-33/DEC/SU-SE-01-/HYDERABAD