


105 x 60 x 3
002063

Digitally signed by Sanjeev Sharma
Date: 2024.06.04 14:19:18 +05'30'

1. ALL DIMENSION ARE IN MM 2. UNSPECIFIED RADIUS:-0.30 3. TOLERANCE WILL BE AS PER DIN EN 755-9:2016 UNLESS OTHERWISE SPECIFIED						TWIST & STRAIGHTNESS :- *** mm/mtrs CRITICAL DIMENSIONS :-  EXPOSED SURFACE :-		CUSTOMER NAME :- PART DESCRIPTION :- GANGWAY SDW EXTRUSION PROFILE																																	
UNSPECIFIED TOLERANCES WILL BE IN ACCORDANCE WITH DIN EN 755-9:2016						AREA: 1046.536 Sqmm WEIGHT: 2.826 kg/mtr. PERIMETER: 345.547 mm. PROFILE CCD : Ø119mm		S.No Customer Drawing No Rev. Date		SCALE:- 1:1 DATE: 15/05/2024 DRAWN BY: KR CHECKED BY: RK APPROVED BY: MA																															
<table border="1"> <thead> <tr> <th>Tolerance on Cross Sectional</th> <th>0 -10</th> <th>10-25</th> <th>25-50</th> <th>50-100</th> <th>100-150</th> </tr> </thead> <tbody> <tr> <td>0 <CCD< 100</td> <td>+/-0.25</td> <td>+/-0.3</td> <td>+/-0.5</td> <td>+/-0.7</td> <td>---</td> </tr> <tr> <td>100<CCD< 200</td> <td>+/-0.30</td> <td>+/-0.4</td> <td>+/-0.6</td> <td>+/-0.9</td> <td>+/-1.1</td> </tr> </tbody> </table>						Tolerance on Cross Sectional	0 -10	10-25	25-50	50-100	100-150	0 <CCD< 100	+/-0.25	+/-0.3	+/-0.5	+/-0.7	---	100<CCD< 200	+/-0.30	+/-0.4	+/-0.6	+/-0.9	+/-1.1	DIE TYPE HOLLOW		Enquiry No: OSP 1347		SECTION NO:													
Tolerance on Cross Sectional	0 -10	10-25	25-50	50-100	100-150																																				
0 <CCD< 100	+/-0.25	+/-0.3	+/-0.5	+/-0.7	---																																				
100<CCD< 200	+/-0.30	+/-0.4	+/-0.6	+/-0.9	+/-1.1																																				
<table border="1"> <thead> <tr> <th>NOMINAL WALL THICKNESS</th> <th>0-1.5</th> <th>1.5-3.0</th> <th>3.0-6.0</th> <th>6.0-10.0</th> <th>10.0-15.0</th> </tr> </thead> <tbody> <tr> <td>SOLID CCD 0< 100</td> <td>+/-0.15</td> <td>+/-0.15</td> <td>+/-0.2</td> <td>+/-0.25</td> <td>+/-0.30</td> </tr> <tr> <td>SOLID CCD 100<300</td> <td>+/-0.20</td> <td>+/-0.25</td> <td>+/-0.30</td> <td>+/-0.35</td> <td>+/-0.40</td> </tr> <tr> <td>HOLLOW CCD 0<100</td> <td>+/-0.20</td> <td>+/-0.25</td> <td>+/-0.40</td> <td>+/-0.60</td> <td>+/-0.80</td> </tr> <tr> <td>HOLLOW CCD 100<300</td> <td>+/-0.30</td> <td>+/-0.40</td> <td>+/-0.60</td> <td>+/-0.80</td> <td>+/-1.00</td> </tr> </tbody> </table>						NOMINAL WALL THICKNESS	0-1.5	1.5-3.0	3.0-6.0	6.0-10.0	10.0-15.0	SOLID CCD 0< 100	+/-0.15	+/-0.15	+/-0.2	+/-0.25	+/-0.30	SOLID CCD 100<300	+/-0.20	+/-0.25	+/-0.30	+/-0.35	+/-0.40	HOLLOW CCD 0<100	+/-0.20	+/-0.25	+/-0.40	+/-0.60	+/-0.80	HOLLOW CCD 100<300	+/-0.30	+/-0.40	+/-0.60	+/-0.80	+/-1.00	Revision Status Revision No. Description Date		ALLOY & TEMPER: 6063 T5		Rev: 00	
NOMINAL WALL THICKNESS	0-1.5	1.5-3.0	3.0-6.0	6.0-10.0	10.0-15.0																																				
SOLID CCD 0< 100	+/-0.15	+/-0.15	+/-0.2	+/-0.25	+/-0.30																																				
SOLID CCD 100<300	+/-0.20	+/-0.25	+/-0.30	+/-0.35	+/-0.40																																				
HOLLOW CCD 0<100	+/-0.20	+/-0.25	+/-0.40	+/-0.60	+/-0.80																																				
HOLLOW CCD 100<300	+/-0.30	+/-0.40	+/-0.60	+/-0.80	+/-1.00																																				