



** ALLOY / MATERIAL GRADE 63400W AS PER IS: 733-1983

LOCATION:-P1 - 1HOLE
 ALL DIMENSION ARE IN M.M.
 UNSPECIFIED CORNER RADIUS:0.40

TOL. AS PER IS: 3965-1981
 UNLESS SPECIFIED

TWIST = ±1/2°/300 M.M./M.
 STRAIGHTNESS = 1.50 M.M./MTR.
 ANGULARITY = ±2°

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY SAMPLE & DRG.		227		PARTY NAME		M/S AIKON TECHNOLOGY (FARIDABAD)		REF:-AS PER FAX. ON Dt.-05.03.09						
002	(C)	+0.30	+0.40	DRAWN	DHARMVIR	05.03.09	AREA	578.00	MM ²					
		TOL-0.00 WAS -0.00								CHECKED	2.4.09	WEIGHT	1.560	KG/M.
		AS PER EMAIL ON Dt.-27.03.09								APPROVED	2.4.09	WT. RANGE	-----	Kg/12'
	(B)	+0.65	+0.80	SCALE	1:1&2:1	DATE	ALLOY	63400-W **						
		TOL-0.00 WAS -0.00												
	(A)	+0.75	+0.80											
		TOL-0.00 WAS -0.00												
001	(REF.)	AS PER IOM Dt.-12.03.09		CRITICAL DIM.		*	MAL NO	11011						
REV. STATUS	REV. NO.	DESCRIPTION		SIGN DATE	PERIMETER	INT.	EXT.	SEC.NO.	D-4635					
		REVISION					308.50							