



Q02165

Q02122

LOCATION:-
ALL DIMENSION ARE IN mm.
UNSPECIFIED CORNER RADIUS 0.40

PLEASE SPECIFY THE EXPOSED SURFACE
TOL AS PER GB/T5237.1-2017
UNLESS SPECIFIED

HIGH STRENGTH ALLOY 6063T6
TWIST=±1/4°/300 MM/M
FLATNESS= WIDTH X0.005mm
STRAIGHTNESS= 1.5 MM/MTR.
ANGULARITY=±0.5°

M. R. INDUSTRIES V.K.I. AREA, JAIPUR.

| PARTY SAMPLE & DRG. | | | PARTY NAME:- | | | REF:- | Dt. |
|---------------------|----------|-------------|--------------|--------------|---------|-----------|--------------|
| | | | | DRAWN | | AREA | 159.0 MM/SQ. |
| | | | | CHECKED | | WEIGHT | 0.42 KG/mtr |
| | | | | APPROVED | | WT. RANGE | 1.555kg/12' |
| | | | | SCALE | 1:1,3:1 | DATE | ALLOY |
| 00 | (REF) | | | CRITICAL DIM | * | | MAL NO |
| REV. STATUS | REV. NO. | DESCRIPTION | SIGN DATE | PERIMETER | INT. | 178.6 | SEC NO. |
| A4 | | REVISION | | EXT. | 337.7 | | 6268 |