


Actual



SHUTTER COVER

 $\Delta N_2 =$

ALL DIMENSIONS ARE IN M.M.
R.D. CORNER RADIUS:0.40

TOL. AS PER B.S.1474:1987
UNLESS SPECIFIED

TWIST = $1/4^{\circ}/300$ M.M./M.
 RAUGHTNESS = 1.5 M.M./MT
 GULARITY = 2°

STRAIGHTNESS = 1.5 M.M./MT
ANGULARITY = 2°

UNLESS SPECIFIED
STRAIGHTNESS= 1.5 M.M./MT
ANGULARITY = 2°

USYS INDUSTRIES LIMITED BHIWADI RAJASTHAN-301019

DRG

PARTY NAME	M/s. S.M.
DRAWN	REF:-AS PER

INDUSTRIES LIMITED BHIWADI RAJASTHAN-301019		ANGULARITY = 2°	
DRG	PARTY NAME M/s. S.M.	REF:-AS PER PARTY DRG. DI.- 30.03.20K	
	DRAWN A.K.SHARMA	01.04.06	AREA: 31.0 MM
	CHECKED <i>ERI</i>	3.4.06	WEIGHT: 0.083 KG/M
	APPROVED <i>ERI</i>	3.4.06	WT. RANGE: --- Kg/12
	SCALE 1:1&7:1	DATE	ALLOY: 6063
	CRITICAL DIM. *		
DESCRIPTION	SIGN		
REVISION	DATE		