



WITH DIN ISO 2768 - 1 class C = Coarse		0.5-3	±0.2	0.5-3	±0.4	at 10	±1°30'	ALL DIMENSION ARE IN MM.				UNSPECIFIED CORNER RADIUS: 0.40MM.					
		3-6	±0.3	3-6	±1.0	10-50	±1°	PERIMETER	INT. 181.71 mm	EXT. 279.70 mm	AREA	395.42 mm <sup>2</sup>		CRITICAL DIM.	*	WEIGHT	
Dimension Longitudinal		6-30	±0.5	6-30	±2.0	50-120	±1°30'						SEC. TYPE	HOLLOW	WT. RANGE	0.970-1.200 kg/M	
Chamfer & Radius		3-6	±0.3	3-6	±1.0	10-50	±1°						ANGULARITY	±2°	ALLOY	6063	
Degrees & Minutes		0.5-3	±0.2	0.5-3	±0.4	at 10	±1°30'						TWIST	1/4°/300mm/M	MMM NO.	11366	
		REV. STATUS	REV. NO.	DESCRIPTION	DATE	SIGN	STRAIGHTNESS	1.7 mm/M		SEC NO.	801-0067						
		REVISION					FLATNESS										
		DRAWN	18.04.11	APPROVED			CAVITY	1									
		CHECKED	JITENDER	SCALE		1:1	DIE DIA	250 mm									
CUSTOMER NAME:-																	
CUSTOMER REF.NO.:-																	