



ALL DIMENSION ARE IN MM.

UNSPECIFIED CORNER RADIUS: 0.40MM.

WITH DIN ISO 2768 - 1 class C = Coarse				30-120	120-400	400-1000				
Dimension Longitudinal	Chamfer & Radius	Degrees & Minutes	at 10	±1°30'	±1.2	±2.0	PERIMETER	INT. 135.91 _{mm}	EXT. 226.18 _{mm}	AREA 272.97 mm ²
0.5 - 3 ±0.2	0.5 - 3 ±0.4	at 10 ±1°30'	10-50 ±1°	50-120 ±1°30'	30-120 ±0.8	120-400 ±1.2	CRITICAL DIM.	*	WEIGHT	
3 - 6 ±0.3	3 - 6 ±1.0	10-50 ±1°	50-120 ±1°30'	120-400 over 400 ±0°15'	6 - 30 ±0.5	30-120 ±0.8	SEC. TYPE	HOLLOW	WT. RANGE	0.635-0.800 kg/M
6 - 30 ±0.5	6 - 30 ±2.0	50-120 ±1°30'	120-400 over 400 ±0°15'		6 - 30 ±0.5	30-120 ±0.8	ANGULARITY	±1°	ALLOY	6063 - T6
							TWIST	±1.0mm/M.	MMM NO.	11075
							STRAIGHTNESS	±1.7mm/M.	SEC NO.	800-0034
							FLATNESS	±0.1mm/M.		
							CAVITY	1		
							DIE DIA	180 mm		

CUSTOMER NAME:-

CUSTOMER REF.NO.:-