



P-21036-1

25398



☐ MARKED DIMENSIONS ARE IMPORTANT

TOLERANCES ON OVERALL WIDTHS & WIDTHS ACROSS FLATS OF BARS, & REGULAR SECTIONS

UPTO 6.40mm - ±0.20	UPTO 32.0mm - ±0.38	UPTO 120.0mm - ±0.85	1. STRAIGHTNESS=1.7mm/M 2. TWIST=1.7mm/M 3. ANGULARITY= ±2° 4. FLATNESS =0.007xWIDTH
UPTO 10.0mm - ±0.23	UPTO 50.0mm - ±0.46	UPTO 160.0mm - ±1.02	
UPTO 12.0mm - ±0.25	UPTO 60.0mm - ±0.53	UPTO 200.0mm - ±1.14	
UPTO 16.0mm - ±0.28	UPTO 80.0mm - ±0.69	UPTO 250.0mm - ±1.40	
UPTO 25.0mm - ±0.30	UPTO 100.0mm - ±0.75	UPTO 300.0mm - ±1.65	



SYMBOL OF QUALITY
AN ISO 9001 COMPANY

JINDAL ALUMINIUM LTD.
BANGALORE-560073 (INDIA)

	NAME	DATE
DRAWN	DARPAN	17-06-2020
CHECKED		
APPROVED	B.NATARAJA	30-06-2020
SCALE		1:1
AREA mm ²		892.161
PERIMETER mm.		338.646
WEIGHT kg/m		2.409
DRAWING No.		SECTION No.
P-21036-1		-
25398		25398

1. ALL DIMENSIONS ARE IN mm.
2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm.
3. TOLERANCES WILL BE AS PER IS:3965-1981 , UNLESS OTHERWISE SPECIFIED

PARTY'S NAME	PROGRESSIVE ENGINEERING CO.
PARTY'S DRAWING No.	AE PER AUTOCAD DRAWING
ALLOY & TEMPER	6082 T6
DESCRIPTION	LINKBOX DOUBLE UNIVERSAL NAUTRAL / EARTH TERMINATION (SINGLE BOLT)