



1. GENERAL WALL THICKNESS = 2.50mm
2. F = FULL RADIUS (12 PLACES)
3. R = RADIUS 2mm (20 PLACES)
4. r = RADIUS 1mm (12 PLACES)
5. REMOVE ALL SHARP EDGES & BURRS
5. ALL EXTERNAL SURFACES ARE VISIBLE

**JINDAL**  
 SYMBOL OF QUALITY  
 AN ISO 9002 COMPANY

**JINDAL ALUMINIUM LTD.**  
 BANGALORE-560073 (INDIA)

1. ALL DIMENSIONS ARE IN mm.
2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm.
3. TOLERANCES WILL BE AS PER IS:6477-1983 UNLESS OTHERWISE SPECIFIED

PARTY'S NAME	BLOW PLAST ERGONOMICS LTD, NAGPUR	NAME	RAGHAVENDRA	DATE	24-07-2004
PARTY'S DRAWING No.	TT801889	DRAWN		CHECKED	
ALLOY & TEMPER	6063 T6	APPROVED		SCALE	1:1
DESCRIPTION	MISC. TUBE	AREA mm <sup>2</sup>	1826.504	PERIMETER mm.	483.111
		WEIGHT kg/m	4.932	DRAWING No.	SECTION No.
				P-4915-1	-
				X338	X338
				28927	28927