


* = R1.0 mm (16 PLACES)

TOLERANCES ON OVERALL DIMENSIONS OF HOLLOW SECTIONS

UPTO 20.0mm - ±0.30	UPTO 80.0mm - ±0.70	UPTO 180.0mm - ±1.27
UPTO 30.0mm - ±0.38	UPTO 100.0mm - ±0.80	UPTO 200.0mm - ±1.40
UPTO 40.0mm - ±0.45	UPTO 120.0mm - ±0.90	UPTO 225.0mm - ±1.52
UPTO 50.0mm - ±0.52	UPTO 140.0mm - ±1.00	
UPTO 60.0mm - ±0.60	UPTO 160.0mm - ±1.14	

1. STRAIGHTNESS=1.7mm/M
2. TWIST=1.7mm/M
3. ANGULARITY= ±2°
4. FLATNESS =0.006xWIDTH

 <p>SYMBOL OF QUALITY AN ISO 9001 COMPANY</p>		<p>JINDAL ALUMINIUM LTD. BANGALORE-560073 (INDIA)</p>		DRAWN	J.P.KAUSHIK	DATE	20-09-2017
<p>1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm. 3. TOLERANCES WILL BE AS PER IS:6477-1983 UNLESS OTHERWISE SPECIFIED</p>				CHECKED			
<p>PARTY'S NAME GENERAL CATEGORY, DELHI MARKET</p>				APPROVED	B.NATARAJA		03-10-2017
<p>PARTY'S DRAWING No. AS PER SKETCH</p>				SCALE			1:1
<p>ALLOY & TEMPER 6082 T6</p>				AREA mm ²			4658.104
<p>DESCRIPTION MISC. SECTION</p>				PERIMETER mm.			766.3
				WEIGHT kg/m			12.577
				DRAWING No.			12.577
				SECTION No.			
				DRAWING No.	P-14914-3		
				SECTION No.	35122		

