



TOLERANCE ON CUT LENGTH = ± 5 mm

PLEASE SPECIFY THE EXPOSED SURFACE

TOL. AS PER BS EN 755-8:2008
UNLESS SPECIFIED

TWIST = NA
FLATNESS = NA
STRAIGHTNESS = 1.50 M.M./MTR.
ANGULARITY = NA

LOCATION:-P1-IHOLE
ALL DIMENSION ARE IN mm.
UNSPECIFIED CORNER RADIUS:0.40

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY SAMPLE & DRG.		B-175		PARTY NAME M/S CUE DEE			REF:- AS PER EMAIL DT.- 13.07.18		
				DRAWN	VIVEK YADAV	13.07.18	AREA	537.20	MM ²
		Alloy 6005-T6 was 6082-T6		CHECKED			WEIGHT	1.450	KG/M.
	(B)	Tol. +/-0.20 was +/-0.30		APPROVED			WT. RANGE	-----	KG/12
001	(A)	Tol. +/-0.45 was +/-0.60		SCALE	1:1	DATE	ALLOY	6005-T6	
	(REF.)	AS PER EMAIL DT.- 18.07.18		CRITICAL DIM.	*		MAL NO	17274	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	170.00	SEC.NO.	B-175	
A4		REVISION			EXT.	188.40			