



NOTE:-

V = 0.30X90° (V GROOVE)

LOCATION:- P1 - 2HOLE

ALL DIMENSION ARE IN M.M.

UNSPECIFIED CORNER RADIUS: 0.40

TOL. AS PER B.S.1474:1987
UNLESS SPECIFIED

TWIST = 1/4°/300M.M.M.
STRAIGHTNESS = 1.5 M.M./MTR.
ANGULARITY = ±2°

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY SAMPLE & DRG. C35988		PARTY NAME CARYAIRE			REF:- AS PER EMAIL ON Dt-16.01.09			
(D)	DIM. 4.75 WAS 2.00		DRAWN	DHARMVIR	17.01.09	AREA	192.00	MM ²
(C)	+0.26 +0.30 TOL. -0.10 WAS -0.10	See	CHECKED	See	27.09	WEIGHT	0.518	KG/M.
(B)	+0.50 +0.50 TOL. -0.00 WAS -0.10	See	APPROVED	See	27.09	WT. RANGE	-----	Kg/12'
(A)	TOL. ±0.30 WAS ±0.40		SCALE	1:1&2:1	DATE	ALLOY	6063-T5	
001	(REF.) AS PER EMAIL ON Dt.-28.04.09		CRITICAL DIM. *			MAL NO	10922	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	-----	SEC.NO.	D-4700
		REVISION			EXT.	246.55		