



**NOTE:-**

1. LENGTH:- 2000 ± 10mm.
2. THERE SHOULD BE NO DENT/SCRATCHES

LOCATION:-P2 - 4HOLE  
 ALL DIMENSION ARE IN M.M.  
 UNSPECIFIED CORNER RADIUS:0.40

TOL. AS PER BS EN 755-9:2008  
 UNLESS SPECIFIED

TWIST  $\square = \pm 1/4^\circ / 300$  M.M./M.  
 STRAIGHTNESS  $\square = 1.50$  M.M./MTR.  
 ANGULARITY  $\square = \pm 1.5^\circ$

**INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019**

PARTY SAMPLE & DRG. RMGEN146		PARTY NAME M/S PRANAV VIKAS (I) PVT. LTD.		REF:- AS PER DIE ORDER FORM Dt.-26.10.10			
			DRAWN	DHARMVIR	27.10.10	AREA	71.16 MM <sup>2</sup>
			CHECKED	<i>[Signature]</i>		WEIGHT	0.193 KG/M.
			APPROVED		WT. RANGE	-----	Kg/12'
	(A)	ADD TOL. R15 ± 0.30mm.	SCALE	1:1 & 5:1	DATE	ALLOY	6063-T6
00	(REF.)	AS PER EMAIL DT.10.10.010	CRITICAL DIM. *			MAL NO	11951
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	SEC.NO.	D-5089
		REVISION			EXT.		