



NOTE:-

$r = 0.50R$
 $R = 1.00R$

PLEASE SPECIFY THE EXPOSED SURFACE

LOCATION:-P2 - 1HOLE
 ALL DIMENSION ARE IN mm.
 UNSPECIFIED CORNER RADIUS:0.40

TOL. AS PER BS EN 755-9:2008
 UNLESS SPECIFIED

TWIST=±1/4°/300 M.M./M.
 FLATNESS= WIDTH X 0.005mm.
 STRAIGHTNESS= 1.50 M.M./MTR.
 ANGULARITY=±1.5°

JINDAL ALUMINIUM LTD. BHIWADI-301019

PARTY SAMPLE & DRG. RM0K05P1C01		PARTY NAME M/S PRANAV VIKAS (I) LTD.			REF:- AS PER EMAIL ON Dt.-12.02.14			
			DRAWN	DHARMVIR	13.02.14	AREA	266.50	MM ²
			CHECKED	<i>SB</i>	13.3.14	WEIGHT	0.720	KG/M.
	(B)	TOL. ±0.20 WAS ±0.25mm.	APPROVED	<i>SB</i>	13.3.14	WT. RANGE	-----	Kg/12
	(A)	TOL. ^{+0.40} -0.20 WAS ±0.40mm.	SCALE	1:1 & 2:1	DATE	ALLOY	6063-T6	
001	(REF.)	AS PER EMAIL ON Dt.-14.02.14	CRITICAL DIM.	*		MAL NO	14112	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	SEC.NO.	D-6063	
A4		REVISION			EXT.			182.66