



LOCATION:-P1 - 1HOLE
 ALL DIMENSION ARE IN mm.
 UNSPECIFIED CORNER RADIUS:0.40

PLEASE SPECIFY THE EXPOSED SURFACE

TOL. AS PER BS EN 755-9:2008
 UNLESS SPECIFIED

TWIST=±1/4°/300 M.M/M.
 FLATNESS= WIDTH X 0.005mm.
 STRAIGHTNESS= 1.50 M.M/MTR.
 ANGULARITY=±1.5°

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY SAMPLE & DRG. X418		PARTY NAME M/S SAXON FLUID SEALING DEVICES			REF:- AS PER DRG. D.-07.01.15		
			DRAWN	DHARMVIR	07.01.15	AREA	1102.90 MM ²
			CHECKED	Sanil	16.2.15	WEIGHT	2.978 KG/M.
			APPROVED			WT. RANGE	----- Kg/12
			SCALE	1:1 & 2:1	DATE	ALLOY	6082-T6
00	(REF.)		CRITICAL DIM.	*		MAL NO	14647
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	SEC.NO.	D-6302
A4		REVISION			EXT.	174.61	