



NOTE:-
 1:1.00R
 R=2.00R

LOCATION: - P-1 - I-HOLE
 ALL DIMENSIONS ARE IN mm.
 UNSPECIFIED CORNER RADIUS: 0.40

PLEASE SPECIFY THE EXPOSED SURFACE
 TOL. AS PER IS EN 755-9:2008
 UNLESS SPECIFIED

TWIST = ±1/4°/300MM/M.M.
 FLATNESS = WIDTH X 0.005mm.
 STRAIGHTNESS = 1.50MM/M.MTR.
 ANGULARITY = ±1.5°

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY NAME	M/S SARRK INTERNATIONAL	REF:-	AS PER EMAIL ON DA-02.09.15
PARTY SAMPLE & DRG. EXT	EXT162862803	DATE	03.09.15
DRAWN	DHARMANVAR	AREA	412.82 MM ²
CHECKED	SAROT	WEIGHT	1.115 KG/M.
APPROVED	SAROT	WT. RANGE	----- Kg/12
SCALE	1:1 & 4:1	ALLOY	6063-T6
CRITICAL DIM.	*	MAL. NO.	15127
REV. STATUS	00 (REF.)	DATE	
REV. NO.			
DESCRIPTION			
REVISION			
43			

SEC. NO. D-6498