



LOCATION:-P3 - 6HOLE  
 ALL DIMENSION ARE IN mm.  
 UNSPECIFIED CORNER RADIUS:0.40

**PLEASE SPECIFY THE EXPOSED SURFACE**

TOL. AS PER BS EN 755-9:2008  
 UNLESS SPECIFIED

TWIST=±1/4°/300 M.M./M.  
 FLATNESS= WIDTH X 0.005mm.  
 STRAIGHTNESS= 1.50 M.M./MTR.  
 ANGULARITY=±1.5°

**INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019**

PARTY SAMPLE & DRG.		SAMPLE		PARTY NAME M/S PERFECT SOLUTIONS			REF:- AS PER IOM Dt.-11.02.16		
				DRAWN	DHARMVIR	16.02.16	AREA	28.02	MM <sup>2</sup>
				CHECKED	<i>[Signature]</i>		WEIGHT	0.076	KG/M.
				APPROVED	<i>[Signature]</i>	12/4/16	WT. RANGE	-----	Kg/12
				SCALE	1:1 & 5:1	DATE	ALLOY	6063-T6	
00	(REF.)			CRITICAL DIM.	*		MAL NO	15375	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.		SEC.NO.	D-6618	
A4		REVISION			EXT.	47.68			