



NOTE:-

$O = 0.41R$

F = Full Radius

TWIST = $\pm 1/4^\circ/300$ M.M./M.

FLATNESS = WIDTH X 0.005mm.

STRAIGHTNESS = 1.50 M.M./MTR.

ANGULARITY = $\pm 1.5^\circ$

PLEASE SPECIFY THE EXPOSED SURFACE

LOCATION:-P3 - 6HOLE
ALL DIMENSION ARE IN mm.
UNSPECIFIED CORNER RADIUS:0.40

TOL. AS PER BS EN 755-9:2008
UNLESS SPECIFIED

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

| | | | | | | | | |
|------------------------------------|----------|------------------------------|---------------|-----------|-------------------------------|-----------|---------|-----------------|
| PARTY SAMPLE & DRG. HS350-00084-00 | | PARTY NAME M/S UNGER INDIA | | | REF:- AS PER MOM Dt.-01.12.15 | | | |
| | (D) | DIM. 11.00 WAS 11.08mm. | DRAWN | DHARMVIR | 02.12.15 | AREA | 29.92 | MM ² |
| | (C) | DIM. 17.00 WAS 16.80mm. | | | | | | |
| | (B) | DIM. 7.00 WAS 6.90mm. | CHECKED | | | WEIGHT | 0.081 | KG/M. |
| | (A) | DIM. 1.00 WAS 0.90mm. | | | | | | |
| 001 | | AS PER EMAIL ON Dt.-12.03.16 | APPROVED | | | WT. RANGE | ----- | Kg/12' |
| | | SHAPE MODIFIED | SCALE | 1:1 & 5:1 | DATE | ALLOY | 6063-T6 | |
| 001 | (REF.) | AS PER DRG. Dt.-12.03.16 | CRITICAL DIM. | * | | MAL NO | 15249 | |
| REV. STATUS | REV. NO. | DESCRIPTION | SIGN DATE | PERIMETER | INT. | SEC.NO. | D-6644 | |
| A4 | | REVISION | | | EXT. | | | |