



NOTE:-

$r = 0.30R$

$C = 0.80 \times 45^\circ$ (CHAMFER)

LOCATION:-P1-6 HOLE
 ALL DIMENSION ARE IN mm.
 UNSPECIFIED CORNER RADIUS:0.40

PLEASE SPECIFY THE EXPOSED SURFACE

TOL. AS PER BS EN 755-9:2008
 UNLESS SPECIFIED

TWIST=±1/4°/300 M.M./M.
 FLATNESS= WIDTH X 0.005mm.
 STRAIGHTNESS= 1.50 M.M./MTR.
 ANGULARITY=±1.5°

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY SAMPLE & DRG. AD 50.69		PARTY NAME M/S GREEN FACADE SOLUTION			REF:- AS PER EMAIL ON Dt.-11.07.16			
			DRAWN	DHARMVIR	14.07.16	AREA	58.75	MM ²
			CHECKED	S.P.	20/8/16	WEIGHT	0.159	KG/M.
			APPROVED			WT. RANGE	-----	Kg/12
			SCALE	1:1 & 5:1	DATE	ALLOY	6063-T6	
00	(REF.)		CRITICAL DIM. *			MAL NO	15615	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	SEC.NO.	D-6692	
A4		REVISION			EXT.			