



NOTE:-
F = Full Radius
Unmarked Radius is 0.30R

PLEASE SPECIFY THE EXPOSED SURFACE

LOCATION:-PI-IHOLE
ALL DIMENSION ARE IN mm.
UNSPECIFIED CORNER RADIUS:0.40

TOL. AS PER BS EN 755-9:2008
UNLESS SPECIFIED

TWIST = ±1/4°/300 M.M.
FLATNESS = WIDTH X 0.005mm.
STRAIGHTNESS = 1.50 M.M./MTR.
ANGULARITY = ±1.5°

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019									
PARTY SAMPLE & DRG.		SAMPLE (10)	PARTY NAME		M/S PERFECT SOLUTIONS		REF:- AS PER IOM Dt.- 27.09.16		
				DRAWN	VIVEK YADAV	08.10.16	AREA	511.11 MM ²	
				CHECKED			WEIGHT	1.380 KG/M.	
001	(B)	DIM. 29.0 WAS 26.20		APPROVED			WT. RANGE	----- Kg/12	
	(A)	DIM. 30 WAS 23.50		SCALE	2:1,4:1,5:1 & 8:1	DATE	ALLOY	6063-T6	
	(REF.)	AS PER EMAIL DT.- 09.12.16		CRITICAL DIM.	*		MAL NO	15745	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	265.08	SEC.NO.	D-6871	
A3		RI	N		EXT.	288.97			