



V = VEE GROOVE 0.5x90° (1 PLACE)
 ----- EXPOSED SURFACE

TOLERANCES ON OVERALL WIDTHS & WIDTHS ACROSS FLATS OF BARS, & REGULAR SECTIONS

UPTO 6.40mm - ±0.20	UPTO 32.0mm - ±0.38	UPTO 120.0mm - ±0.85
UPTO 10.0mm - ±0.23	UPTO 50.0mm - ±0.46	UPTO 160.0mm - ±1.02
UPTO 12.0mm - ±0.25	UPTO 60.0mm - ±0.53	UPTO 200.0mm - ±1.14
UPTO 16.0mm - ±0.28	UPTO 80.0mm - ±0.69	UPTO 250.0mm - ±1.40
UPTO 25.0mm - ±0.30	UPTO 100.0mm - ±0.75	UPTO 300.0mm - ±1.65

<p>SYMBOL OF QUALITY AN ISO 9001 COMPANY</p>	JINDAL ALUMINIUM LTD.		DRAWN	NAME	DATE
	BANGALORE-560073 (INDIA)		CHECKED	PARVESH	05-12-2014
1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm. 3. TOLERANCES WILL BE AS PER IS:3965-1981, UNLESS OTHERWISE SPECIFIED		APPROVED	S.S.GARG	16-12-2014	

PARTY'S NAME	ALUFIT (INDIA) PRIVATE LIMITED, BANGALORE	SCALE	1:1
PARTY'S DRAWING No.	AS PER AUTOCAD DRAWING-GD-D1 & REQUIREMENT	AREA mm ²	1081
ALLOY & TEMPER	6063 T6	PERIMETER mm.	744.894
DESCRIPTION	CURTAIN WALL SECTION-BEADING-2	WEIGHT kg/m	2.919
		DRAWING No.	SECTION No.
		P-14233	-
		E0252	E0252