



\* = RADIUS 1 mm. (21 PLACES)  
F = FULL RADIUS (10 PLACES)

PLEASE SPECIFY THE EXPOSED SURFACE IN THE DRAWING WHEREVER BETTER FINISH REQUIRED.  
TOLERANCES ON OVERALL WIDTHS & WIDTHS ACROSS FLATS OF BARS, & REGULAR SECTIONS

UPTO 6.40mm - ±0.20	UPTO 32.0mm - ±0.38	UPTO 120.0mm - ±0.85
UPTO 10.0mm - ±0.23	UPTO 50.0mm - ±0.46	UPTO 160.0mm - ±1.02
UPTO 12.0mm - ±0.25	UPTO 60.0mm - ±0.53	UPTO 200.0mm - ±1.14
UPTO 16.0mm - ±0.28	UPTO 80.0mm - ±0.69	UPTO 250.0mm - ±1.40
UPTO 25.0mm - ±0.30	UPTO 100.0mm - ±0.75	UPTO 300.0mm - ±1.65

 SYMBOL OF QUALITY AN ISO 9001 COMPANY	<b>JINDAL ALUMINIUM LTD.</b> BANGALORE-560073 (INDIA)	
	DRAWN	J.P. KAUSHIK 05-06-2017
1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm. 3. TOLERANCES WILL BE AS PER IS:6477-1983, UNLESS OTHERWISE SPECIFIED	CHECKED	
PARTY'S NAME	ALUFIT (INDIA) PRIVATE LIMITED, BANGALORE	
PARTY'S DRAWING No.	AS PER AutocAD DRAWING-CR-15	
ALLOY & TEMPER	6063 T6	
DESCRIPTION	CURTAIN WALL SECTION-CILL TRANSOM	

SCALE	1:1
AREA mm <sup>2</sup>	1486.025
PERIMETER mm.	581.771
WEIGHT kg/m	4.012
DRAWING No.	SECTION No.
P-17188-1	-
E0706	E0706