



F = FULL RADIUS (12 PLACES)
 * = RADIUS 1.0 (12 PLACES)

TOLERANCES ON OVERALL WIDTHS & WIDTHS ACROSS FLATS OF BARS, & REGULAR SECTIONS

UPTO 6.40mm - ±0.20	UPTO 32.0mm - ±0.38	UPTO 120.0mm - ±0.85
UPTO 10.0mm - ±0.23	UPTO 50.0mm - ±0.46	UPTO 160.0mm - ±1.02
UPTO 12.0mm - ±0.25	UPTO 60.0mm - ±0.53	UPTO 200.0mm - ±1.14
UPTO 16.0mm - ±0.28	UPTO 80.0mm - ±0.69	UPTO 250.0mm - ±1.40
UPTO 25.0mm - ±0.30	UPTO 100.0mm - ±0.75	UPTO 300.0mm - ±1.65

<p>SYMBOL OF QUALITY AN ISO 9001 COMPANY</p>	<p>JINDAL ALUMINIUM LTD.</p> <p>BANGALORE-560073 (INDIA)</p>	
	<p>1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm. 3. TOLERANCES WILL BE AS PER IS:6477-1983 UNLESS OTHERWISE SPECIFIED</p>	<p>SCALE 1:1</p> <p>AREA mm² 1619.415</p> <p>PERIMETER mm. 624.94</p> <p>WEIGHT kg/m 4.372</p>

PARTY'S NAME	ALUFIT (INDIA) PVT. LTD., BANGALORE	DRAWING No.	P-17980-1	SECTION No.	-
PARTY'S DRAWING No.	AL-SV-06	DRAWING No.	E0816	SECTION No.	E0816
ALLOY & TEMPER	6063 T6				
DESCRIPTION	MID TRANSOM SECTION				