


TOLERANCES ON OVERALL WIDTHS & WIDTHS ACROSS FLATS OF BARS, & REGULAR SECTIONS

UPTO 6.40mm - ±0.20	UPTO 32.0mm - ±0.38	UPTO 120.0mm - ±0.85	1. STRAIGHTNESS=1.0mm/M
UPTO 10.0mm - ±0.23	UPTO 50.0mm - ±0.46	UPTO 160.0mm - ±1.02	2. TWIST=1.0mm/M
UPTO 12.0mm - ±0.25	UPTO 60.0mm - ±0.53	UPTO 200.0mm - ±1.14	3. ANGULARITY = ±1°
UPTO 16.0mm - ±0.28	UPTO 80.0mm - ±0.69	UPTO 250.0mm - ±1.40	4. FLATNESS = 0.007xWIDTH
UPTO 25.0mm - ±0.30	UPTO 100.0mm - ±0.75	UPTO 300.0mm - ±1.65	

 SYMBOL OF QUALITY AN ISO 9001 COMPANY		JINDAL ALUMINIUM LTD. BANGALORE-560073 (INDIA)	
1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm. 3. TOLERANCES WILL BE AS PER IS:3965-1981 UNLESS OTHERWISE SPECIFIED			
PARTY'S NAME	ALUFIT (INDIA) PVT. LTD., BANGALORE		
PARTY'S DRAWING No.	WTC-DIE-01		
ALLOY & TEMPER	6005 T6		
DESCRIPTION	FLOOR MOUNTED BRACKET SECTION		
DRAWN		NAME	DATE
CHECKED		J.P.KAUSHIK	06-07-2018
APPROVED		B.MATARAJA	14-07-2018
SCALE		1:1	
AREA		mm ²	5277.275
PERIMETER		mm.	836.103
WEIGHT		kg/m	14.249
DRAWING No.		SECTION No.	
P-18393		-	
E0862		E0862	