

NOTE:-

F= FULL RADIUS (1 PLACE)

PROUND OFF ALL SHARP CORNERS WITH 0.50 mm.

- TOLERANCE CHART CD = CIRCUMSCRIBING CIRCLE

 DIMENSION | CD≤100 | 100<CD≤200 | 200<CD≤300 | 300<CD≤500 | UPTO 10mm 10.0 -25.0 25.0 -50.0 50.0 -100 100 - 150 150 - 200 200 - 300 300 - 450 ±0.40 ±0.60 ±0.90 ±1.30 ±0.30 ±0.40 ±0.60 ±0.25 ±0.30 ±0.35 ±0.50 ±0.50 ±0.80 ±0.90 ±1.10 ±0.70 ±1.50 ±1.30 ±1.10 ±1.3 ± 1.50 ±1.80 ±1.70 ±2.10 ±2.80
 - Q02391

 CONTROLLED COPY
- 1. STRAIGHTNESS= 1.7mm/M
- 2. TWIST= 1.7mm/M
- 3. ANGULARITY= ±2°
- 4. FLATNESS= 0.007xWIDTH

			NAME	DATE
(JINDAL)	JINDAL ALUMINIUM LTD.	DRAWN	ASHUTOSH	24-09-2024
		CHECKED	PARVESH	17-10-2024
SYMBOL OF QUALITY AN ISO 9001 COMPANY	BHIWADI-301019 (INDIA)	APPROVED	J.N.RAI	17-10-2024
1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.50 mm. 3. TOLERANCES WILL BE AS PER BS:EN-755-9 , UNLESS OTHERWISE SPECIFIED		SCALE		2:1
		AREA mm ²		117.051
		PERIMETER	mm.	178.2
PARTY'S NAME	RUDRA METAL	WEIGHT kg/	/m	0.316
		DRAWING	No. SE	CTION No.
PARTY'S DRAWING No.	AS PER DRAWING-101202	P-JAL-B-748 70		00003069
1110V 0 TEMPER	PRODUCT CODE:-050	G102867 G1		02867
ALLOY & TEMPER	6063 T6			
DESCRIPTION	KITCHEN CABINET SECTION			