



NOTE:-

- $O = 0.50R$
- $\bullet = 1.00R$
- $R = 1.50R$
- $V = 0.5X1.0X90^\circ$

TOLERANCE ON CUT LENGTH = $\pm 5mm$.

LOCATION-P4-1HOLE
 ALL DIMENSION ARE IN M.M.
 UNSPECIFIED CORNER RADIUS:0.40

PLEASE SPECIFY THE EXPOSED SURFACE

TOL. AS PER BS EN 755-9:2008
 UNLESS SPECIFIED

TWIST = $1/4^\circ/300$ M.M.
 FLATNESS = WIDTH X 0.005mm.
 STRAIGHTNESS = 1.50 M.M./MTR.
 ANGULARITY = $\pm 1.5^\circ$

INDO ALUSYS INDUSTRIES LIMITED BHIWADI RAJASTHAN - 301019

PARTY SAMPLE & DRG.		DRAWING	PARTY NAME		M/s. Pivot Solutions	REF:-		AS PER EMAIL DT.- 20.06.18	
				DRAWN	VIVEK YADAV	20.06.18	AREA	1422.20	MM ²
				CHECKED	<i>[Signature]</i>		WEIGHT	3.840	KG/M.
001	(B)	Dim. 43.75 was 43.50	<i>[Signature]</i>	APPROVED	<i>[Signature]</i>		WT. RANGEA	-----	Kg/12'
	(A)	Thick. 3.1+/-0.25 was 2.8+/-0.25		SCALE	1:1	DATE	ALLOY	6063-T6	
	(REF.)	As per Email & Party Disc. on Tele. dt.- 29.06.18		CRITICAL DIM.	*		MAL NO.	17222	
REV. STATUS	REV. NO.	DESCRIPTION	SIGN DATE	PERIMETER	INT.	-----	SEC.NO.	G-881	
		REVISION			EXT.	931.00			