



V = VEE GROOVE 0.3X90° (1 PLACE)  
 F = FULL RADIUS (8 PLACES)

TOLERANCE CHART CD = CIRCUMSCRIBING CIRCLE

DIMENSION	CD<100	100<CD<200	200<CD<300	300<CD<500
UP TO 10mm	±0.25	±0.30	±0.35	±0.40
10.0 - 25.0	±0.30	±0.40	±0.50	±0.60
25.0 - 50.0	±0.50	±0.60	±0.80	±0.90
50.0 - 100	±0.70	±0.90	±1.10	±1.30
100 - 150	-	±1.10	±1.30	±1.50
150 - 200	-	±1.3	±1.50	±1.80
200 - 300	-	-	±1.50	±2.10
300 - 450	-	-	±1.70	±2.80

<p>SYMBOL OF QUALITY AN ISO 9001 COMPANY</p>	<p><b>JINDAL ALUMINIUM LTD.</b></p> <p>BANGALORE-560073 (INDIA)</p>	
	DRAWN	NAME
CHECKED	J.P.KAUSHIK	DATE
APPROVED	B.NATARAJA	02-04-2019

1. ALL DIMENSIONS ARE IN mm.
2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm.
3. TOLERANCES WILL BE AS PER BS:EN-755-9 , UNLESS OTHERWISE SPECIFIED

PARTY'S NAME	VENTEX INC, CANADA
PARTY'S DRAWING No.	EH16708A
ALLOY & TEMPER	6063 T6
DESCRIPTION	MISC SECTION
SCALE	2:1
AREA mm <sup>2</sup>	684.993
PERIMETER mm.	320.031
WEIGHT kg/m	1.849
DRAWING No.	P-19024
SECTION No.	X2497