



TOLERANCE CHART CD = CIRCUMSCRIBING CIRCLE

CD ≤ 100	100 < CD ≤ 200	200 < CD ≤ 300	300 < CD ≤ 500
UP TO 10mm - ±0.25	±0.30	±0.35	±0.40
10.0 - 25.0 - ±0.30	±0.40	±0.50	±0.60
25.0 - 50.0 - ±0.50	±0.60	±0.80	±0.90
50.0 - 100.0 - ±0.70	±0.90	±1.10	±1.30
100 - 150 - -	±1.10	±1.30	±1.50
150 - 200 - -	±1.30	±1.50	±1.80
200 - 300 - -	-	±1.50	±2.10
300 - 450 - -	-	±1.70	±2.80

x = 0.20 RADIUS (30 PLACES)
 * = 0.30 RADIUS (54 PLACES)
 R = 0.50 RADIUS (14 PLACES)
 V = V GROOVE 0.50x90° (6 PLACES)
 F = FULL RADIUS (8 PLACES)

SYMBOL OF QUALITY
 AN ISO 9001 COMPANY

JINDAL ALUMINIUM LTD.
 BANGALORE-560073 (INDIA)

1. ALL DIMENSIONS ARE IN mm.
2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm.
3. TOLERANCES WILL BE AS PER BS:EN-755-9, UNLESS OTHERWISE SPECIFIED

PARTY'S NAME	PERFECT GLAZE, UNITED KINGDOM	SCALE	2:1
PARTY'S DRAWING No.	TW 10	AREA mm ²	471.694
ALLOY & TEMPER	6063 T6	PERIMETER mm.	358.035
DESCRIPTION	WINDOW SECTION	WEIGHT kg/m	1.274
		DRAWING No.	SECTION No.
		P-20941-1	-
		X2652	X2652

