



NOTE:-

- r= 0.50RADIUS (6 PLACES)**
- R= 1.0RADIUS (4 PLACES)**
- F= FULL RADIUS (4 PLACES)**
- *= 0.5 RADIUS x 0.3 DEEP (5 PLACES)**
- V= 0.4x90° V-GROOVE (4 PLACES)**

- 1. STRAIGHTNESS= 1.7mm/M
- 2. TWIST= 1.7mm/M
- 3. ANGULARITY= ±2°
- 4. FLATNESS= 0.007xWIDTH

(Q00597)

<p>SYMBOL OF QUALITY AN ISO 9001 COMPANY</p>	<p>JINDAL ALUMINIUM LTD. BHIWADI-301019 (INDIA)</p>		NAME	DATE
	<p>1. ALL DIMENSIONS ARE IN mm. 2. ROUND OFF ALL SHARP CORNERS WITH 0.40 mm. 3. TOLERANCES WILL BE AS PER BS:EN-755-9 , UNLESS OTHERWISE SPECIFIED</p>	<p>DRAWN ASHUTOSH 22-06-2023</p> <p>CHECKED <i>[Signature]</i> 11/7/23</p> <p>APPROVED <i>[Signature]</i> 11/07/23</p> <p>SCALE 1.5:1</p> <p>AREA mm² 584.94</p> <p>PERIMETER mm. 465.67</p> <p>WEIGHT kg/m 1.580</p>		
PARTY'S NAME	M/S. EUBIQ HEALTHCARE & LIGHTING GURURAM		DRAWING No.	SECTION No.
PARTY'S DRAWING No.	AS PER SAMPLE		P-JAL-B-251	
ALLOY & TEMPER	6063-T6		XE0003	XE0003
DESCRIPTION	INDUSTRIAL SECTION			